

DRAWN BY: TM 21/11/23 CONSTRUCTION A3 (297x420) RAWING NO: EN 6765 - 000 - 023 REV: 00

SIGN VISIBILITY: 50m DISTANCE BETWEEN SIGNS: 20m SIGNS SIZE RECTANGULAR - MIN. 600mm IGNS SIZE CIRCULAR - MIN. 600mm CONE HEIGHT - MIN. 750mm APER CONE SPACING

**DESIGN PARAMETERS** 

1(III)

50km/h

ONGITUDINAL CONE SPACING LANE - 45°; HS - N/Am SAFETY ZONE: LONGITUDINAL - 5m; LATERAL-0.5m

JNOBSTRUCTED WIDTH: MAXIMUM LENGTH OF SHUTTLE: 500m MINIMUM LANE WIDTH: 3.0m

TRAFFIC LIGHTS/ STOP & GO



## SITE SPECIFIC NOTES

- STOP & GO OPERATIVES AND PEDESTRIAN MARSHAL TO MANAGE PEDESTRIANS WHERE APPLICABLE.
  PEDESTRIAN RAMPS TO BE PROVIDED WHERE APPLICABLE.
- TRAFFIC LIGHTS TO BE CONTROLLED MANUALLY DURING PEAK ALL STOP OR ALL RED FOR TRAFFIC LIGHTS TO BE IMPLEMENTED TO
- ALLOW PEDESTRIANS APPROACHING FROM SPRINGMOUNT WOODS CROSS R639.
- SECTION OF WALL TO BE REMOVED AND SUITABLE SURFACE PROVIDED TO ALLOW PEDESTRIAN ACCESS VIA MEADOWBROOK.
- TTM TO BE REMOVED AFTER WORKING HOURS.
- ADDITIONAL WK062 QUEUES LIKELY TO INSTALLED IF TAILBACKS

## **LEGEND**

- TEMPORARY TRAFFIC SIGN

- TRAFFIC CONES

- SAFETY ZONE

- WORKS AREA

- PEDESTRIAN ROUTE

- PEDESTRIAN BARRIER/FENCE

DATE BY B DESCRIPTION

SORENSEN

**GLASHABOY FLOOD RELIEF SCHEME** GLANMIRE, CO.CORK

AREA 2 HAZELWOOD - PHASE 2G SHUTTLE SYSTEM

CHECKED: EΒ TAGE:

CONSTRUCTION SKILLS REGISTRATION CARD 'SIGNING, LIGHTING, AND GUARDING AT ROADWORKS' CONSTRUCTION REGULATIONS 2006 AND 2013-2021 CONSTRUCTION REGULATIONS 3) THE TTOS TO DETERMINE EXACT POSITION OF SIGNS CONSIDERING THE SITE SPECIFICS.

TERMINALS MUST BE KEPT CLEAR, AND NO WORKS SHOULD BE UNDERTAKEN IN THAT EXCLUSION ZONE AND SAFETY ZONE.

14) ALL INFORMATION CONTAINED IN THIS DRAWING SHOULD BE CHECKED VERIFIED AND APPROVED PRIOR TO ANY STAGE OF CONSTRUCTION.

TEL: +353868118317