



Coirib go Cósta

Scéim Faoisimh Tuilte Chathair na Gaillimhe
Galway City Flood Relief Scheme

Galway City Flood Relief Scheme

Hydrology Report

January 2023



Tionscadal Éireann
Project Ireland
2040



OPW

Óifig na n-Obair Poiblí
Office of Public Works



Comhairle Cathrach na Gaillimhe
Galway City Council

ARUP



OPW

Oifig na
nOibreacha Poiblí
Office of Public Works

GALWAY CITY FLOOD RELIEF SCHEME

HYDROLOGY REPORT

JANUARY 2023

Table of Contents

1	Executive Summary	1
1.1	Introduction.....	1
1.2	Flood Flow Rating Review of Key Hydrometric Stations	1
1.3	Hydrological Estimation Points	1
1.4	Return period flood flows.....	2
1.5	Design Flood Hydrographs	2
1.6	Tidal Flood Analysis	3
1.7	Storm Surge Design Profile	3
1.8	Joint Probability Analysis.....	4
1.9	Trend Analysis of Corrib Flows.....	4
1.10	Recommendations	5
2	Introduction.....	6
2.1	Background.....	6
2.2	Corrib Catchment	8
2.2.1	General description.....	8
2.3	Galway Salmon Weir Sluice Barrage	13
2.4	Lough Corrib.....	15
2.4.1	Lakes within the Corrib Catchment.....	15
2.4.2	Inflow Tributaries to Lough Corrib.....	15
2.5	Tributaries discharging to the River Corrib downstream of the Lake	17
3	Data Collection	20
3.1	Introduction.....	20
3.2	Hydrometric Gauges.....	22
3.3	Review of Physical Catchment Descriptor datasets	25
3.4	CFRAM review.....	25
3.5	Hydrogeology and Groundwater.....	29
4	Hydrometric Data Collation and Review	36
4.1	Past Fluvial Flood Events.....	36
4.2	Past Tidal Flood Events	40
4.3	Hydrometric data collation.....	41
4.4	Rating Review.....	43

4.4.1	Claregalway Gauge (30012)	43
4.4.2	Wolfe Tone Bridge Gauge (30061).....	51
4.4.3	Flood Rating For Dangan Gauge (30098)	62
4.5	Hydrometric Gauging.....	66
5	Flood Flow Frequency Analysis	67
5.1	Introduction.....	67
5.2	Index Flood method.....	67
5.3	FSU Flood estimation method of QMED	67
5.4	Flood Frequency Analysis to estimate Q_T	68
5.4.1	Gauged Sites.....	69
5.4.2	Ungauged Sites	70
5.4.3	Annual Maxima Series.....	71
5.4.4	Flood Frequency Distributions	71
5.4.5	Fitting of statistical distributions	73
5.4.6	Estimation of Flood Quantiles.....	74
5.5	At-Site Frequency Analysis of River Corrib Gauges	75
5.5.1	River Corrib Wolfe Tone (30061) AM series	75
5.5.2	River Corrib Dangan (30098) AM series	78
5.5.3	River Corrib At-Site Return Period Q_T Estimates for Galway City.....	80
5.5.4	River Corrib At-Site Standard Error for Q_T	81
5.5.5	River Corrib flood Growth Curve from at-Site analysis.....	83
5.6	River Corrib Pooled Analysis.....	83
5.6.1	Introduction.....	83
5.6.2	Selection of Pooling Group.....	84
5.7	OPW FSU 2021 Q-T Atlas.....	93
5.8	QMED Pivotal Site Adjustment Estimate	99
5.9	Recommended Design Flows and Growth Factor for River Corrib	99
5.10	Flood Estimation for Small Ungauged Catchments	102
5.10.1	Introduction.....	102
5.10.2	Flood Flow estimates – IH124 Equation	102
5.10.3	Other flood study ungauged catchment flood estimation equations	105
5.10.4	Flood Flow Estimates - Rational Method.....	106
5.10.5	Conclusion	107

6	Trend Analysis	108
6.1	Introduction.....	108
6.2	Exploratory Data Analysis Methods	109
6.3	Statistical Test Methods Used in Trend Analysis	109
6.4	Discussion	109
6.5	Trend Analysis Conclusions	110
7	Tidal Flood Frequency Analysis	134
7.1	Introduction.....	134
7.2	Astronomical Tides.....	134
7.3	Tidal Storm Surge Effects	136
7.4	Historical Maximum Tide levels	137
7.5	Tidal Flood Records	142
7.6	Statistical Analysis of Tides.....	146
7.7	Irish Coastal Wave and Water Level Modelling Study (ICWWS 2018) Tidal Estimates..	153
7.8	Recommended Design Tide Levels.....	154
7.9	Design Tidal Flood Profile.....	156
7.10	Design Surge Profile.....	157
7.11	Timing of Surge Profile	169
7.12	Recommended Design Tidal Flood Profile for Galway City	187
8	Joint Probability Analysis.....	188
8.1	Introduction.....	188
8.2	Tidal and Corrib Flood Flow Joint Probability Relationship.	189
8.3	Short Duration Rainfall and Corrib Flood flows.....	193
8.4	Short Duration Rainfall and Tidal Highwater levels.....	195
9	Design Hydrograph determination	198
9.1	Introduction.....	198
9.2	FSU Hydrograph Width Method	198
9.3	Fitted Hydrograph Shape Method	199
9.4	Recommended Design Flood Hydrographs.....	201
9.5	Hydrograph Estimation for Small Tributaries	203
10	Future Change allowances.....	207
10.1	Introduction.....	207
10.2	Potential Climate Changes	207

10.2.1	General	207
10.2.2	Sea Level Rise	208
10.2.3	Sea State	210
10.2.4	Fluvial Flooding.....	211
10.3	Potential Land-Use Changes.....	211
10.4	Urban Development.....	212
10.5	Recommended Future Change Allowances.....	213
11	Hydrological Estimation Points (HEPs) and recommended Design Flows.....	214
11.1	Selection of HEPS.....	214
11.2	PCDs and Design Flows at HEPs	215
12	Uncertainty in Flow and Tide Prediction	221
12.1	Introduction.....	221
12.2	Statistical Standard Error.....	221
12.3	Model Error	222
12.4	Measurement Error	222
12.5	Trend in the AM Series.....	223
12.6	Conclusion	223
13	References.....	226
14	Appendix 1 - Annual Maximum flood Series	228
15	Appendix 2 - Flow Rating Data	265

List of Figures

Figure 2-1	Galway City Flood Relief Scheme Area Boundary.....	7
Figure 2-2	EPA Designated Coastal (Navy Blue) and Transitional / Estuarine (Green) waters at Galway City.....	9
Figure 2-3	River Corrib Catchment Map to Wolfe Tone Bridge.....	10
Figure 2-4	Corrib Arterial Drainage Channel.....	11
Figure 2-5	Terryland Stream catchment area of 9km2 discharging to the sea via swallow-holes at Castlegar.	12
Figure 2-6	Main Catchments to Lough Corrib.....	16
Figure 2-7	Sruffaunacashlaun Stream catchment area from Lidar mapping.....	18
Figure 2-8	Terryland Drainage Basin Contour Map and Features	19
Figure 2-9	Terryland Stream Surface Drainage Area Contributing to flood flows.....	19
Figure 3-1	Relevant Hydrometric flow and water level only Gauging Stations within Corrib Catchment.....	23
Figure 3-2	Hydrometric flow and water level only Gauging Stations within Galway City Scheme Area	23
Figure 3-3	Daily Read Rain Gauges for the Corrib Catchment	24
Figure 3-4	CFRAM Design Hydrograph Shape for the Corrib at Wolfe Tone Bridge from HWA and the FSR time to peak and design storm method included for comparison.....	28
Figure 3-5	Bedrock Aquifer within the Corrib Catchment.....	30
Figure 3-6	Groundwater Vulnerability within the Corrib Catchment.....	31
Figure 3-7	Quaternary Geology of the Corrib Catchment.....	32
Figure 3-8	Groundwater Recharge mapping for Corrib Catchment (mm per annum)	33
Figure 3-9	Corine 2018 Land Use mapping for Corrib Catchment.....	34
Figure 3-10	OPW Arterial Drainage Channels and benefitting Lands	35
Figure 4-1	Annual maximum lake level series for Lough Corrib gauged at Annaghdown Pier (1972 to 2019), Cong Pier (1972 to 2019) and at Angligham (1980 to 2019).....	36
Figure 4-2	Annual Maximum lake level series at Caher Pier (30081) in Lough Mask from (1952 to 2019).....	37
Figure 4-3	Estimated AM flood flow series for the River Corrib at Wolfe Tone Bridge Gauge (30061) 1950 to 2020.....	37
Figure 4-4	Gauged 15minute and daily average flow hydrograph for River Corrib at Dangan for November 2009 flood Event.....	38
Figure 4-5	Gauged 15minute and daily average flow hydrograph for River Corrib at Dangan for Dec 2015 / Jan 2016 flood event	39
Figure 4-6	Gauged 15minute and daily average flow hydrograph for River Corrib at Dangan for February 2020 flood event.....	39
Figure 4-7	Oranmore Gauge AM tidal heights (hydrological Years 1982 to 2019)	41
Figure 4-8	EPA Rating Date and rating relationships for Claregalway gauge (1989 to 2020)	45
Figure 4-9	EPA Rating Date for combined periods 2012 to 2016 and post 2016 (H stage height above Staff zero of 5.60m OD Malin).....	46
Figure 4-10	Model Rating Results for post Claregalway flood relief scheme (2017 to 2021).....	48
Figure 4-11	Recommended Rating Relationship for Flood Flow Estimation in the River Clare at Claregalway Gauge (30012) - Post flood relief scheme (2017 to present).....	49
Figure 4-12	Estimated AM flood flow Series for River Clare at Claregalway Gauge (1996 to 2020)	49
Figure 4-13	Various OPW rating curves and rating measurement data for Wolfe Tone Bridge since 1972	53
Figure 4-14	OPW Rating measurements and rating Curves for Wolfe Tone Bridge 1972 to 2021	53
Figure 4-15	Current OPW rating curve and rating measurements for Wolfe Tone Bridge (2009 to present)	54
Figure 4-16	OPW Rating Fitted to reliable flow measurements for period 2009 to 2020	55
Figure 4-17	Location of relevant survey section to represent the Hydrometric Gauge at Wolfe Tone Bridge.....	56
Figure 4-18	Computed longitudinal Flood Level Profile for QMED flow	57
Figure 4-19	Modelled QMED at Wolfe Tone Gauging station - Cross-Section 30Corr00070	57
Figure 4-20	Modelled Rating for Wolfe Tone Bridge gauging station using varying roughness n with flow rate Q.....	58
Figure 4-21	Modelled Ratings for Wolfe Tone Bridge gauging station using constant a constant Manning roughness n.....	58
Figure 4-22	Estimated AM flood Flow Series for Wolfe Tone Bridge Gauge using full record length	60

Figure 4-23	Fitting of Flood rating Relationship for Dangan Stations (with all Gates open on the Salmon Weir Barrage).....	64
Figure 4-24	Recommended Rating Relationship for Flood Flows at Dangan Gauge when all Gates are open at the Salmon Weir Barrage.	64
Figure 4-25	Estimated Annual Maximum Flow Series for River Corrib At Dangan (30098) (1986 – 2020).....	65
Figure 5-1	Statistical fit of selected probability distributions to the AM Flood data For River Corrib at Wolfe Tone Gauge (full series)	75
Figure 5-2	Statistical fit of other statistical probability distributions to the AM Flood data For River Corrib at Wolfe Tone Gauge (full series).....	76
Figure 5-3	Statistical fit of selected probability distributions to the AM Flood data For River Corrib at Wolfe Tone Gauge (1972 to 2019).....	77
Figure 5-4	Statistical fit of other statistical probability distributions to the AM Flood data For River Corrib at Wolfe Tone Gauge (full series).....	77
Figure 5-5	Statistical fit of selected probability distributions to the AM Flood data For River Corrib at Dangan Gauge (1986 to 2020)	79
Figure 5-6	Statistical fit of other statistical probability distributions to the AM Flood data For River Corrib at Wolfe Tone Gauge (full series).....	79
Figure 5-7	Estimated Return Period Flood Flows QT for River Corrib at Galway City with 67-percentile statistical confidence intervals from at-Site EV1 statistical Analysis (representing average between Wolfe Tone (N=48) and Dangan (N=34) Stations).	82
Figure 5-8	Fitting of GEV (3-parameter) and EV1 (2-parameter) Distributions to Corrib Regional Pooling group	86
Figure 5-9	Fitting of GEV (3-parameter) and EV1 (2-parameter) Distributions to Pooling group based on FSU 3-parameter selection	90
Figure 5-10	Fitting of GEV (3-parameter) and EV1 (2-parameter) Distributions to Pooling group based on 4-parameter Selection	92
Figure 5-11	Location of Node 30_3419_2 located upstream of the Salmon Weir Barrage adjacent to NUI Galway and Dike Road	95
Figure 5-12	Fitting of GEV (3-parameter) and EV1 (2-parameter) Distributions to Pooling group produced from the OPW Q-T atlas 2021 Method.....	98
Figure 5-13	Estimated Flood Growth Curves for River Corrib from at-site and Pooled statistical analysis	100
Figure 6-1	Time Series of the AM Flood Flow Ranking for Corrib at Wolfe Tone Gauge (30061) (1950 to 2020)	112
Figure 6-2	AM Flood Flow Series for Corrib at Wolfe Tone Gauge (30061) (1950 to 2020)	112
Figure 6-3	Time Series of the AM Flood Flow Ranking for Corrib at Wolfe Tone Gauge (30061) (1972 to 2020)	113
Figure 6-4	AM Flood Flow Series for Corrib at Wolfe Tone Gauge (30061) (1972 to 2020)	113
Figure 6-5	Time Series of the AM Flood Flow Ranking for Corrib at Dangan Gauge (30098) (1986 to 2020).....	114
Figure 6-6	AM Flood Flow Series for Corrib at Dangan Gauge (30098) (1986 to 2020)	114
Figure 6-7	Time Series of the AM Flood Levels Ranking for Lough Corrib at Angligham Gauge (30089) (1981 to 2019).....	115
Figure 6-8	AM Flood Level Series for Lough Corrib at Angligham Gauge (30089) (1981 to 2019)....	115
Figure 6-9	Time Series of the AM Flood Levels Ranking for Lough Corrib at Anaghdown Pier Gauge (30083) (1972 to 2019).....	116
Figure 6-10	AM Flood Level Series for Lough Corrib at Anaghdown Pier Gauge (30083) (1972 to 2019).....	116
Figure 6-11	Time Series of the AM Flood Levels Ranking for Lough Corrib at Cong Pier Gauge (30084) (1972 to 2019).....	117
Figure 6-12	Time Series of the AM Flood Levels for Lough Corrib at Cong Pier Gauge (30084) (1972 to 2019).....	117
Figure 6-13	Time Series of the AM Flood Levels Ranking for Lough Mask at Cahir Pier Gauge (30081) (1952 to 2019).....	118
Figure 6-14	AM Flood Level Series for Lough Mask at Cahir Pier Gauge (30081) (1952 to 2019)	118
Figure 6-15	Time Series of the AM Flood Levels Ranking for Lough Carra at Burriscarra Gauge (30082) (1981 to 2019).....	119
Figure 6-16	AM Flood Level Series for Lough Carra at Burriscarra Gauge (30082) (1981 to 2019)	119

Figure 6-17	Time Series of the AM Flood Flow Ranking for Clare River at Ballygaddy Gauge (30007) (1974 to 2019)	120
Figure 6-18	AM Flood Flow Series for Clare River at Ballygaddy Gauge (30007) (1974 to 2019)	120
Figure 6-19	Time Series of the AM Flood Flow Ranking for Clare River at Corrofin Gauge (30004) (1964 to 2019)	121
Figure 6-20	AM Flood Flow Series for Clare River at Corrofin Gauge (30004) (1964 to 2020)	121
Figure 6-21	Time Series of the AM Flood Flow Ranking for Clare River at Claregalway Gauge (30012) (1996 to 2020)	122
Figure 6-22	AM Flood Flow Series for Clare River at Claregalway Gauge (30012) (1996 to 2020)	122
Figure 6-23	Time Series of the AM Flood Flow Ranking for Lough Allen Outflow at Bellantra Sluices (26030) (1941 to 2020)	123
Figure 6-24	AM Flood Flow Series for Lough Allen Outflow at Bellantra Sluices (26030) (1941 to 2020)	123
Figure 6-25	Time Series of the AM Flood Flow Ranking for River Shannon at Athlone Gauge (26027) (1952 to 2019)	124
Figure 6-26	AM Flood Flow Series for River Shannon at Athlone Gauge (26027) (1952 to 2019)	124
Figure 6-27	Time Series of the AM Flood Flow Ranking for River Shannon at Banagher Gauge (25017) (1950 to 2019)	125
Figure 6-28	AM Flood Flow Series for River Shannon at Banagher Gauge (25017) (1950 to 2019)	125
Figure 6-29	Time Series of the AM Flood Flow Ranking for River Fergus at Ballycorey Gauge (27002) (1952 to 2019)	126
Figure 6-30	AM Flood Flow Series for River Fergus at Ballycorey Gauge (27002) (1952 to 2019)	126
Figure 6-31	Time Series of the AM Flood Flow Ranking for River Erne at Belturbet Gauge (36019) (1958 to 2019)	127
Figure 6-32	AM Flood Flow Series for River Erne at Belturbet Gauge (36019) (1958 to 2019)	127
Figure 6-33	Time Series of the AM Flood Flow Ranking for River Moy at Rahans Gauge (34001) (1968 to 2019)	128
Figure 6-34	AM Flood Flow Series for River Moy at Rahans Gauge (34001) (1968 to 2019)	128
Figure 6-35	Time Series of the AM Flood Flow Ranking for Cong Canal at Cong Weir Gauge (30031) (1979 to 2019)	129
Figure 6-36	AM Flood Level Series for Cong Canal at Cong Weir Gauge (30084) (1979 to 2019)	129
Figure 6-37	Time Series of the AM Flood Flow Ranking for Robe River at Foxhill Gauge (30005) (1955 to 2019)	130
Figure 6-38	AM Flood Flow Series for Robe River at Foxhill Gauge (30005) (1955 to 2019)	130
Figure 6-39	Time Series of the AM Flood Flow Ranking for Shrle River at Ower Bridge Gauge (30002) (1974 to 2019)	131
Figure 6-40	AM Flood Flow Series for Shrle River at Ower Bridge Gauge (30002) (1974 to 2019)	131
Figure 7-1	Tidal Flood Event recorded at Galway Port Gauge on the 3rd January 2014	138
Figure 7-2	Tidal Flood Event recorded at Galway Port Gauge on the 1st February 2014	139
Figure 7-3	Tidal Flood Event recorded at Galway Port Gauge on the 2nd January 2018 (Storm Eleanor)	139
Figure 7-4	Tidal Flood Event recorded at Wolfe Tone Bridge Galway City and Oranmore Bridge on the 2nd January 2018 (Storm Eleanor)	140
Figure 7-5	Observed versus Predicted Tides for Galway Port – 3rd Jan 2014 (note surge component is residual level between observed tide less the predicted astronomical tide)	140
Figure 7-6	Observed versus Predicted Tides for Galway Port – 1st February 2014 (note surge component is residual level between observed tide less the predicted astronomical tide)	141
Figure 7-7	Observed versus Predicted Tides for Galway Port - 2nd Jan 2018 (note surge component is residual level between observed tide less the predicted astronomical tide)	141
Figure 7-8	Recorded Annual Maximum Flood Level Series at Galway Port Gauge (29062) from 2007 to 2021	144
Figure 7-9	Recorded Annual Maximum Flood Level Series at Wolfe Tone Bridge Gauge (20015) from 1992 to 2021	145
Figure 7-10	Recorded Annual Maximum Flood Level Series at Oranmore Bridge Gauge (29015) from 1982 to 2021	145
Figure 7-11	Flood Frequency Analysis of the Oranmore Tidal Flood AM series fitting standard hydrological probability distributions	149
Figure 7-12	Flood Frequency Analysis of the Oranmore Tidal Flood AM series fitting other probability distributions	149

Figure 7-13	Flood Frequency Analysis of the Wolfe Tone Tidal Flood AM series fitting a number of standard hydrological probability distributions	150
Figure 7-14	Flood Frequency Analysis of the Wolfe Tone Tidal Flood AM series fitting other probability distributions	150
Figure 7-15	Flood Frequency Analysis of the Galway Port Tidal Flood AM series fitting standard hydrological probability distributions	151
Figure 7-16	Flood Frequency Analysis of the Galway Port Tidal Flood AM series fitting other probability distributions	151
Figure 7-17	Tidal Flooding H – T with 67-percentile upper and lower confidence Intervals based on EV1 analysis of the Oranmore Gauge	152
Figure 7-18	Tidal Flooding H – T with 67-percentile upper and lower confidence Intervals based on EV1 analysis of the Wolfe Tone Gauge	152
Figure 7-19	Tidal Flooding H – T with 67-percentile upper and lower confidence Intervals based on EV1 analysis of the Galway Port Gauge	153
Figure 7-20	Typical Lunar Tidal Series at the Galway Port	156
Figure 7-21	Surge Event 31 March 2011 – Galway Port Gauge	158
Figure 7-22	Surge Event 23 December 2012 – Galway Port Gauge	159
Figure 7-23	Surge Event 18 December 2013 – Galway Port Gauge	159
Figure 7-24	Surge Event 27 December 2013 – Galway Port Gauge	160
Figure 7-25	Surge Event 3 January 2014 – Galway Port Gauge	160
Figure 7-26	Surge Event 1 February 2014 – Galway Port Gauge	161
Figure 7-27	Surge Event 12 February 2014 – Galway Port Gauge	161
Figure 7-28	Surge Event 14 January 2015 – Galway Port Gauge	162
Figure 7-29	Surge Event 18 November 2015 – Galway Port Gauge	162
Figure 7-30	Surge Event 23 February 2015 – Galway Port Gauge	163
Figure 7-31	Surge Event 2 January 2018 – Galway Port Gauge	163
Figure 7-32	Surge Event 19 September 2018 – Galway Port Gauge	164
Figure 7-33	Surge Event 28 November 2018 – Galway Port Gauge	164
Figure 7-34	Surge Event 18 December 2019 – Galway Port Gauge	165
Figure 7-35	Surge Event 13 January 2020 – Galway Port Gauge	165
Figure 7-36	Surge Event 15 February 2020 – Galway Port Gauge	166
Figure 7-37	Surge Event 21 August 2020 – Galway Port Gauge	166
Figure 7-38	Standardised Surge Profiles from the selected 17 storm surge events including the average profile	168
Figure 7-39	Recommended Surge Profile and CFRAM Surge Profile for Galway	168
Figure 7-40	10year design tide based on surge profile peaking at highwater and high Spring tide conditions (2.77m OGSM15)	171
Figure 7-41	200year design tide based on surge profile peaking at highwater and high Spring tide conditions (2.77m OGSM15)	171
Figure 7-42	1000year design tide based on surge profile peaking at highwater and high Spring tide conditions (2.77m OGSM15)	172
Figure 7-43	Return Period Tides for combination of storm surge peaking at highwater and high Spring tide conditions (2.77m OGSM15)	172
Figure 7-44	10year design tide based on surge profile peaking at highwater and mean Spring tide conditions (2.175m OGSM15)	173
Figure 7-45	200year design tide based on surge profile peaking at highwater and mean Spring tide conditions (2.175m OGSM15)	173
Figure 7-46	1000year design tide based on surge profile peaking at highwater and mean Spring tide conditions (2.175m OGSM15)	174
Figure 7-47	Return Period Tides for combination of storm surge peaking at highwater and mean Spring tide conditions (2.175m OGSM15)	174
Figure 7-48	10year design tide based on surge profile peaking at mid-flood and high Spring tide conditions (2.77m OGSM15)	175
Figure 7-49	200year design tide based on surge profile peaking at mid-flood and high Spring tide conditions (2.77m OGSM15)	175
Figure 7-50	1000year design tide based on surge profile peaking at mid-flood and high Spring tide conditions (2.77m OGSM15)	176
Figure 7-51	Return Period Tides for combination of storm surge peaking at mid-flood and high Spring tide conditions (2.77m OGSM15)	176

Figure 7-52	10year design tide based on surge profile peaking at mid-flood and mean Spring tide conditions (2.175m OGSM15).....	177
Figure 7-53	200year design tide based on surge profile peaking at mid-flood and mean Spring tide conditions (2.175m OGSM15).....	177
Figure 7-54	1000year design tide based on surge profile peaking at mid-flood and mean Spring tide conditions (2.175m OGSM15).....	178
Figure 7-55	Return Period Tides for combination of storm surge peaking at mid-flood and mean Spring tide conditions (2.175m OGSM15).....	178
Figure 7-56	10year design tide based on surge profile peaking at mid-ebb and high Spring tide conditions (2.77m OGSM15).....	179
Figure 7-57	200year design tide based on surge profile peaking at mid-ebb and high Spring tide conditions (2.77m OGSM15).....	179
Figure 7-58	1000year design tide based on surge profile peaking at mid-ebb and high Spring tide conditions (2.77m OGSM15).....	180
Figure 7-59	Return Period Tides for combination of storm surge peaking at mid-ebb and high Spring tide conditions (2.77m OGSM15).....	181
Figure 7-60	10year design tide based on surge profile peaking at mid-ebb and mean Spring tide conditions (2.175m OGSM15).....	181
Figure 7-61	200year design tide based on surge profile peaking at mid-ebb and mean Spring tide conditions (2.175m OGSM15).....	181
Figure 7-62	1000year design tide based on surge profile peaking at mid-ebb and mean Spring tide conditions (2.175m OGSM15).....	182
Figure 7-63	Return Period Tides for combination of storm surge peaking at mid-ebb and mean Spring tide conditions (2.175m OGSM15).....	182
Figure 7-64	10year design tide based on surge profile peaking at low water and high Spring tide conditions (2.77m OGSM15).....	183
Figure 7-65	200year design tide based on surge profile peaking at low water and high Spring tide conditions (2.77m OGSM15).....	183
Figure 7-66	1000year design tide based on surge profile peaking at low water and high Spring tide conditions (2.77m OGSM15).....	184
Figure 7-67	Return Period Tides for combination of storm surge peaking at low water and high Spring tide conditions (2.77m OGSM15).....	184
Figure 7-68	10year design tide based on surge profile peaking at low water and mean Spring tide conditions (2.175m OGSM15).....	185
Figure 7-69	200year design tide based on surge profile peaking at low water and mean Spring tide conditions (2.175m OGSM15).....	185
Figure 7-70	1000year design tide based on surge profile peaking at low water and mean Spring tide conditions (2.175m OGSM15).....	186
Figure 7-71	Return Period Tides for combination of storm surge peaking at low water and mean Spring tide conditions (2.175m OGSM15).....	186
Figure 8-1	Time series of Corrib Flows and high tide Levels used in the joint probability analysis for Galway City.....	189
Figure 8-2	Corrib Flows versus maximum Daily High Tide Levels for Galway.....	190
Figure 8-3	Frequency of AM flood events by month for Lough Corrib and Lough Mask.....	191
Figure 8-4	Frequency of AM tidal flood events by month for Inner Galway Bay.....	191
Figure 8-5	Time series of Corrib Flows and maximum daily 1-hour rainfalls used in the joint probability analysis for Galway City.....	194
Figure 8-6	Correlation between Corrib Flows and maximum hourly rainfall depths for Galway.....	194
Figure 8-7	Time series of Tidal Highwater and maximum hourly rainfalls used in the joint probability analysis for Galway City.....	196
Figure 8-8	Correlation between Maximum Tidal height and maximum hourly rainfall depths for Galway.....	196
Figure 9-1	Hydrograph Shape of the three largest recorded flood events from the Dangan Gauge	200
Figure 9-2	Hydrograph Shape based on the Average of the three largest recorded flood events at Dangan gauge (30098).....	200
Figure 9-3	UPO Gamma Curve hydrograph Fit for the Corrib at Dangan.....	201
Figure 9-4	Return Period Design Flow Hydrographs For River Corrib at Galway City.....	202
Figure 9-5	Rain Design Storm Rainfall Profile for Sruffaunacashlaun Stream.....	204
Figure 9-6	Rain Design Storm Rainfall Profile for Terryland Stream.....	204

Figure 9-7	Computed Return Period Flood Hydrographs for Sruffaunacashlaun Stream using FSR Triangular unit Hydrograph with Design Storm Event.....	205
Figure 9-8	Computed Return Period Flood Hydrographs for Terryland Stream using FSR Triangular unit Hydrograph with Design Storm Event.....	205
Figure 9-9	Design flood Hydrograph Shape for Sruffaunacashlaun Stream	206
Figure 9-10	Design flood Hydrograph Shape for Terryland Stream.....	206
Figure 10-1	Monthly mean sea level Rise for the Dublin Port Gauge from 1938 to 2016 (copied from Climate Status Report Ireland (CSRI, 2020).....	210
Figure 11-1	Location of HEP Nodes within the Flood Relief Scheme Area	215

List of Tables

Table 1-1	Return Period Design Corrib Flood Flows and Tidal Flood Level	5
Table 3-1	CFRAM Statistical Distribution Type and parameters for River Corrib at Galway.....	26
Table 3-2	Pooling Group Selected by the CFRAM study for the River Corrib (it is based on the FSU web portal selection of sites)	27
Table 3-3	CFRAM estimated Return Period flows and Growth Factor for the Corrib at Wolfe Tone Bridge.....	27
Table 4-1	Return period estimates of Corrib flood levels at gauge stations for the largest four flood event post the Salmon Weir Barrage	37
Table 4-2	Hydrometric Station references to be used in the flood estimation methods and in constructing a flood growth curve pooling group	42
Table 4-3	List of other hydrometric gauges to be included in the Frequency Analysis as potential Pooling Group Candidates Station.....	42
Table 4-4	River Clare AM Flood Flows at Claregalway using recommended Ratings	50
Table 4-5	OPW Rating Equations for different periods at Wolfe Tone Bridge Gauge	51
Table 4-6	Modelled varying n with flow rate Q to achieve fit with Rating data.	57
Table 4-7	River Corrib Estimated AM Flood Flows at Wolf Tone Bridge (30061) using proposed ratings relationship	60
Table 4-8	River Corrib Estimated AM Flood Flows at Dangan (30098) using proposed ratings Relationship	65
Table 5-1	Probability Distributions included in the flood frequency Analysis	72
Table 5-2	Other Probability Distributions applicable to flood frequency analysis	73
Table 5-3	Computed Return Period Flood Flow Quantiles QT for the River Corrib at Wolfe Tone Gauge (30061) using different probability distributions (1950 to 2020).....	76
Table 5-4	Computed Return Period Flood Flow Quantiles QT for the River Corrib at Wolfe Tone Gauge (30061) using different probability distributions (hydrometric years 1972 to 2020) ..	78
Table 5-5	Computed Return Period Flood Flow Quantiles QT for the River Corrib at Dangan Gauge (30098) using different probability distributions (hydrometric years 1986 to 2020)	80
Table 5-6	Computed Return Period Flood Flow Quantiles QT for the River Corrib at Wolfe Tone Gauge and Dangan Gauges for EV1 distribution.....	80
Table 5-7	Computed EV1 statistical error of flow Quantiles QT for the River Corrib at Wolfe Tone and Dangan Gauges	82
Table 5-8	Computed EV1 flood Growth factor for the River Corrib from At-site Statistical Analysis ..	83
Table 5-9	Regional Pooling group from available Corrib gauges	85
Table 5-10	Pooling group selected using Euclidean distance based on FSU method using AREA, SAAR, and BFISOIL	89
Table 5-11	Pooling group selected using Euclidean distance based on modified FSU method using AREA, SAAR, BFISOIL and FARL	91
Table 5-12:	Selected PCDs and weightings used in Q-T Atlas Pooling group selection.	94
Table 5-13	Estimated Return Period Flood Flows River Corrib at Galway City.....	95
Table 5-14	Pooling group selected using Euclidean distance based on new OPW Q-T Atlas method using S1085, DrainD, SAAR, BFISOIL and FARL (note number of gauged pooling stations considered suitable reduced to 51 stations)	97
Table 5-15	Details of PCDs for River Corrib Reference Node 30_3419_2 (Corr_06)	99

Table 5-16	Estimated Flood Growth factors for River Corrib to Galway City from at-site and various pooled analyses.	100
Table 5-17	Recommended Return Period Growth Factor and Design Flows for the River Corrib to Galway City (Node 30-3419-2)	101
Table 5-18	Estimated Statistical Error associated with Corrib Design Flows	101
Table 5-19	FSR (NERC 1975) National Growth Curve For Ireland.....	104
Table 5-20	Estimated return period flood flow and runoff rates for the Sruffaunacashlaun Stream (without inclusion of FSE)	104
Table 5-21	Estimated return period flood flow and runoff rates for the Sruffaunacashlaun Stream (with inclusion of FSE of 1.65).....	104
Table 5-22	Estimated return period design flows and runoff rates for the Terryland Stream (without inclusion of FSE)	105
Table 5-23	Estimated return period design flows and runoff rates for the Terryland Stream (with inclusion of FSE of 1.65).....	105
Table 5-24	Summary of the PCD parameters for the Sruffaunacashlaun and Terryland Streams	106
Table 5-25	QMED Estimates for the Sruffaunacashlaun and Terryland Streams by various Flood Study Estimation Equations	106
Table 5-26	Peak Flood Flows in the Sruffaunacashlaun Stream by the Rational Method	107
Table 5-27	Computed Peak Flood Flows in Terryland Stream by the Rational Method.....	107
Table 6-1	Trend Analysis Results of Annual Maximum Flood Series at Various Relevant Gauges ...	132
Table 7-1	Tides from Galway Bay Admiralty Chart 1984 (HON, 1993)	135
Table 7-2	Astronomical Tidal elevations at Galway Port Gauge provided by the National Oceanography Centre to Galway Harbour Company (2021).....	136
Table 7-3	Recommended Astronomical Tidal Elevations for Galway City area	136
Table 7-4	Missing periods from the Galway Port Gauge Tidal Level Record 3 March 2007 to 5 May 2022	137
Table 7-5	Annual maximum series of tides at Galway (Wolfe Tone Bridge 30061)	142
Table 7-6	Annual maximum series of tides at Galway Port Gauge (29062)	143
Table 7-7	Annual maximum series of tides at Oranmore (29015)	143
Table 7-8	Return period tide level estimates from at-site frequency analysis using EV1 distribution.	147
Table 7-9	Return period tide level estimates from at-site frequency analysis using LOG EV1 distribution	147
Table 7-10	Computed return period tidal flood levels at relevant nodal points to Oranmore, Galway Port and Bearna from the ICWWS 2018 study (RPS, 2020).....	154
Table 7-11	Comparison between ICWWS predictions and the gauged statistical predictions for Galway Port and Oranmore Gauges.	155
Table 7-12	Recommended Return Period Design Tide Highwater Level HT	155
Table 7-13	Required Surge Height to combine with spring tides producing a highwater level of 2.77m OGSM15.....	156
Table 7-14	Required Surge Height to combine with a mean Spring Tide highwater level of 2.175m OGSM15 to achieve the return period flood heights	157
Table 7-15	Surge Events Exceeding 1m extracted from Available Galway Port Gauge Record (2007 to 2022).....	158
Table 8-1	Statistical correlation and dependence categories	188
Table 8-2	Marginal Return period tidal flood elevations and River Corrib flood flows for Galway City (refer to Sections 5.9 and 7.8)	192
Table 8-3	Estimated Joint and marginal return periods between Corrib Flood Flow and tidal highwater events	192
Table 8-4	Estimated joint exceedance return periods Corrib Flood Flows and tidal highwater levels	193
Table 8-5	Estimated joint exceedance return periods tidal flood levels and Corrib flows.....	193
Table 8-6	Return period short duration rainfall depths for Galway City (extracted from FSU Web Portal 2012)	195
Table 8-7	Estimated Joint and marginal return periods between short duration rainfall and tidal highwater events	197
Table 8-8	Estimated joint exceedance return periods short duration rainfall and tidal highwater levels	197
Table 10-1	Allowances for Future Change Scenarios.....	207
Table 11-1	HEP Node Physical Catchment Descriptors	216
Table 11-2	HEP Node Physical Catchment Descriptors Continued	217
Table 11-3	Return Period Design Flood Flow Magnitudes for HEP-Nodes – Current Scenario	218

Table 11-4	<i>Return Period Design Flood Flow Magnitudes for HEP-Nodes – Mid Range Scenario.....</i>	<i>219</i>
Table 11-5	<i>Return Period Design Flood Flow Magnitudes for HEP-Nodes – High Range Scenario...</i>	<i>220</i>
Table 12-1	<i>Statistical standard error of recommended Flood Growth Curve for River Corrib.....</i>	<i>221</i>
Table 12-2	<i>Percentage statistical standard error for River Corrib Q_T estimate</i>	<i>222</i>
Table 12-3	<i>The River Corrib Design Flows at 67 and 95-percentile confidence intervals.....</i>	<i>222</i>
Table 12-4	<i>Recommended Hydrological uncertainty allowances for Design Flows</i>	<i>223</i>
Table 12-5	<i>Recommended Return Period flood flows for Corrib at Galway City and uncertainty allowance for Sensitivity Testing</i>	<i>224</i>
Table 12-6	<i>Recommended Return Period Tide Flood Levels at Galway City and uncertainty allowance for Sensitivity Testing</i>	<i>224</i>
Table 12-7	<i>Recommended return period flood flow for Corrib at Galway City for current, mid-range and high-end future change cases</i>	<i>224</i>
Table 12-8	<i>Recommended return period tidal flood levels at Galway City for current, mid-range and high-end future change cases</i>	<i>225</i>

Abbreviations

AEP	Annual Exceedance Probability
AFA	Area of Further Assessment
ALLUV	Proportional extent of floodplain alluvial deposit
ALTBAR	Mean elevation of catchment (m)
AM	Annual Maximum
AREA	Catchment Area (km ²)
ARTDRAIN2	Fraction of Catchment that has undergone OPW arterial drainage
BFISOIL	Soil baseflow index (estimate of BFI derived from soils, geology and climate data)
CFRAM	Catchment Flood Risk Assessment Management
C.I.	Confidence interval
CV	Coefficient of Variation
CWI	Catchment wetness index
D _{ij}	Euclidean distance measure from the FSU
DRAIN2	Drainage Density km/km ²
DTM	Digital Terrain Map
EDA	Exploratory data analysis
EPA	Environmental Protection Agency
ESB	Electricity Supply Board
EU	European Union
EV1	Extreme Value Type 1 = Gumbel (a 2-parameter distribution)
FAI	Flood attenuation index
FARL	Index of flood attenuation by reservoirs and lakes
FEH	Flood Estimation Handbook
FLATWET	PCD summarising proportion of time soils expected to be typically quite wet
FOREST	Proportional extent of forest cover FSE Factorial standard error
FRMP	Flood Risk Management Plan
FRS	Flood Relief Scheme
FSE	Factorial standard error
FSR	Flood Studies Report
FSSR	Flood Studies Supplementary Report
FSU	Flood Studies Update

GCC	Galway City Council
GCoCo	Galway County Council
GEV	Generalised Extreme Value (a 3-parameter distribution)
GLO	Generalised Logistic (a 3-parameter distribution)
HA 25	Hydrological Area 26 (Upper Shannon)
HA 26	Hydrological Area 30 (Corrib)
HEC	Hydrological Engineering Centre US Army Corp of Engineers
HEFS	High-End Future Scenario
HEL	Hydro Environmental Ltd.
HEP	Hydrological Estimation Point
HGF	Highest gauged flow
H-skew	Hazen-corrected skewness
iid	Independently and identically distributed
LA	Local Authority
L-CV	Coefficient of L-variation (Hosking and Wallis, 1997)
L-Kurtosis	Coefficient of L-kurtosis (Hosking and Wallis, 1997)
L-Kkewness	Coefficient of L-skewness (Hosking and Wallis, 1997)
LN2	2-parameter lognormal (a distribution)
LN3	3-parameter lognormal (a distribution)
LO	Logistic (a 2-parameter distribution)
LP3	Log Pearson Type 3
Malin	OS Malin Head Datum (Mean Sea level)
mOD	Metres Over Datum (Malin)
MRFS	Mid-Range Future Scenario
MSL	Mainstream length (km)
NERC (UK)	Natural Environment Research Council
NETLEN	Total length of river network above gauge (km)
NWRM	Natural Water Retention Measure
OSi	Ordnance Survey Ireland
OGSM02	Ordnance Survey Geoid Model 2002
OGSM15	Ordnance Survey Geoid Model 2015
OPW	Office of Public Works
PASTURE	Proportional extent of catchment area classed as grassland/pasture/agriculture

PDF	Probability density function
PEAT	Proportional extent of catchment area classified as peat bog
PCD	Physical Catchment Descriptor
Poolbeg	OSi Poolbeg Datum (Lowest Astronomical Tide at Poolbeg Lighthouse)
POT	Peaks Over Threshold series
QBAR	Mean annual maximum flood flow
Qmed	Median annual maximum flood flow
QT	T-year flood
ROI	Region of influence
S1085	Slope of main stream excluding the bottom 10% and top 15% of its length (m/km)
SAAPE	Standard-period average annual potential evapotranspiration (mm)
SAAR	Standard Annual Average Rainfall
SE,se	Statistical standard error (of an estimate)
SOIL	FSR Soil index based on WRAP classifications
SPR	Standard Percentage Runoff
Tb	Time of Base
Tp	Time to peak
Tc	Time of Concentration
TUH	FSR Triangular Unit Hydrograph
UoM	Unit of Management
URBANEXT	Urban Fraction of Catchment
UAF	Urban adjustment factor
UoM	Unit of Management
WI	Waterways Ireland
WRAP	FSR Winter Rainfall Acceptance Potential - soil class

1 Executive Summary

1.1 Introduction

The hydrology study for the proposed Corrib go C6sta (Galway City) Flood Relief Scheme established the best estimates of design return period flood flow magnitudes and associated flood hydrographs within the Galway City Flood Relief Scheme (FRS) Area for the River Corrib and associated local tributaries of the Terryland and Sruffaunacashlaun Streams. Hydrological calculations were completed using best practice FSU methodologies. For this process, suitable HEP locations have been selected and their PCD data updated where required.

The study also examined the tidal flood levels in Inner Galway Bay in respect to extreme storm surge tidal flood events and evaluated combined probabilities with fluvial and pluvial flood events. These fluvial, pluvial and tidal flood estimates are required as inputs to the hydraulic flood model of the estuary, river network and floodplain areas within the FRS area in order to determine the respective return period design flood levels, flow depths and velocities and flood duration .

1.2 Flood Flow Rating Review of Key Hydrometric Stations

A flow rating review of the Wolfe Tone and Claregalway hydrometric stations was carried out to improve the reliability of the flood flow estimates for these stations and to update their respective AM flow series. This rating review was supported by topographic survey and hydraulic modelling. The Wolfe Tone Gauge represents an important hydrometric gauging station for estimating River Corrib flows. The Rating relationship was revised with various ratings produced for different time periods when the stage was measured downstream of the bridge, upstream and more recently reinstalled downstream. The gauge is tidally influenced and extraction of the fluvial component is required at non-tidal periods. The gauge also suffers fluctuations in water level due to turbulence effects particularly towards low tide. The reliability of the flood rating for this site is assessed as moderate. A rating review of the Dangan Gauge on the Corrib as an upstream alternative was carried out for the flood flow range, when all barrage sluice gates are opened. This was found to be generally the case at the annual maximum flow rates. A reliable AM flood flow series for Dangan gauge was produced for the period 1986 to 2020. The index Q_{MED} flow rate measured at Dangan and Wolfe Tone gauges for the same period were within 2.26% of each other, which is within acceptable range of measurement accuracy.

1.3 Hydrological Estimation Points

A total of 22 Hydrological Estimation Points within the Flood Relief Scheme area, 15 on the Corrib River, 5 on the Terryland River and 2 on the Sruffaunacashlaun Stream were selected at key locations for flood flow estimation and input to the hydraulic model. All catchment PCD's at these estimation points were reviewed and revised as necessary.

1.4 Return period flood flows

Return period flood flow estimates for the Corrib were obtained using the FSU index flood method with a pooled flood growth curve. The Flood Studies Update PCD equation was used with a pivotal adjustment to the Q_{MED} value using the gauged Q_{MED} for Dangan and WolfeTone stations. The Q_{MED} estimate for the Corrib to Galway City (HEP 30_3419_2 located 290m upstream of the Salmon Weir Barrage) is 255.7 cumec with a S.E. of 9.2 cumec (or 3.6% of Q_{MED}). This estimate is based on combining the gauged Q_{MED} from Wolfe Tone ($Q_{MED} = 250.6$ cumec for AM period 1972 – 2020) and from Dangan ($Q_{MED} = 260.8$ cumec for AM period 1986 – 2020). This represents a FSU pivotal adjustment factor of 1.608 ($Q_{MED_{gauged}}/Q_{MED_{PCD}}$) for all of the Corrib HEPs within the scheme area.

The recommended flood growth curve for the Corrib is obtained from a 513 station-year pooling group of 9 stations selected using Euclidean distance based on modified FSU method using 4 PCD parameters, namely, AREA, SAAR, BFISOIL and FARL and fitting an EV1 probability distribution. This gives a growth curve very similar to the average of the at-site, Corrib regional, and FSU pooling group growth curves. The growth factor for the 100year flood is 1.704, giving a Q_{100} of 435.7 cumec with an estimated statistical error of 8.31%. It is expected that the design flows developed by fitting an EV1 distribution will be reasonably conservative for the Corrib due to the attenuating effect from Lough Corrib and its extensive regionally important karst aquifer on the eastern side of Lough Corrib, which limits peak flow rates discharging from the lake.

On the small ungauged sub-catchments, peak flow estimation is less certain as Q_{med} has been estimated using ungauged catchment methodology. A suite of hydrological estimation methodologies has been used. The IH124 and Rational methods are recommended for the Terryland and Sruffaunacashlaun streams. Flood flow estimates from both methods are recommended for consideration in the hydraulic modelling of these streams. Hydraulic sensitivity analysis should reflect the high degree of uncertainty associated with the design flood flows for these small, highly urbanised ungauged catchments.

1.5 Design Flood Hydrographs

The design hydrograph for the Corrib was developed using the FSU Hydrograph width method using an UPO Gamma Curve shape with a shape parameter $n = 1.9$ and a shift parameter $Tr = 460$ hours, commencing at a flow rate of 40% of the design flow (i.e. $F = 0.4$) and the standardized ordinates multiplied by the required design flood peak magnitude to produce the design flood hydrograph. The FSR design storm with unit triangular hydrograph method is recommended for small urbanized catchments of the Sruffaunacashlaun Stream and the Terryland River.

1.6 Tidal Flood Analysis

Tidal flood analysis was carried out to provide design tidal flood levels and tidal flood elevation profiles as input to the coastal tide inundation and wave overtopping model analysis for the Flood Relief Scheme. The highest astronomical tide this century occurred on the 29/09/2015 having an estimated astronomical tide height of 2.895m OGS15 based on the Marine Institute astronomical tide forecast model for Galway Port. The lowest astronomical tide based on the Marine Institute model for the record period 2007 to 2022 was found to be -2.967m OD.

The critical larger tidal flooding is produced by Atlantic storm surge events that coincide with higher astronomical spring tide periods. Storm surges of significance occur when an Atlantic depression system is backed by strong gale force westerly winds raising locally the sea water level due to reduced atmospheric pressure and the associated wind shear that tilts the water surface and seiche effects within Inner Galway Bay. This surge can be further pronounced by local wind direction coming around from west to the south towards the peak of the event. Storm surge effects along the West Coast of Ireland can in the more extreme cases increase the normal high-water level by well over 1.5m. From the Galway Port 15year gauge record (2007 to 2022) the estimated maximum surge height of 1.74m occurred on the 18 December 2019.

The ICWWS (2020) estimates the 200year and 1000year coastal flood levels for node W6 (adjacent to Mutton Island) at 4.01m and 4.26m OD Malin respectively. The statistical analysis of the gauged AM tidal flood series gives 200year and 1000year elevations of 3.96m OD and 4.24m OD respectively. The ICWWS predictions includes a flat rate of +0.15m across all of the return periods for local wind/wave and seiche effects on tidal flood levels within inner Galway Bay and recommends an additional model error of 0.15m.

1.7 Storm Surge Design Profile

Analysis of the surge profiles from 17 storm surges exceeding 1m during the record period analysed 2007 to 2022 was carried out to define a design profile shape for the surge event. These surge profiles show considerable variation in shape, some short and sharp and others prolonged. Given the irregularity of the surge profiles and variation between events it is recommended that a smooth, wide profile is used to represent the design surge profile. Different functions, including sine, polynomial and Gamma functions was applied to the data to produce a robust and realistic profile. The selected function was a sine curve to define the sharper section of the profile and the tails of the profile defined by an exponential decay function. The recommended tidal flood profile that retains a degree of conservatism but is not overly conservative is the combination of storm surge profile that peaks at mid-ebb stage coinciding with high spring tides. This profile raises the low water and next high water which may also be important for pumping considerations behind flood defences.

1.8 Joint Probability Analysis

Joint probability analysis was carried out between tidal and Corrib Flood Events giving a 200-year combined probability of a 200-year tidal flood peak of 3.98mOD with a Corrib flow of 145m³/s or a 100year Corrib flood of 435.65m³/s with a 3.01mOD Tidal highwater. Joint probability analysis was also carried out between short duration rainstorm events and Corrib flows and also with tidal highwater levels. The analysis found that there is low correlation between the short duration hourly maximum rainfall and River Corrib flood flows. There is poor to moderate correlation between the short duration hourly maximum rainfall and tidal high tide levels.

1.9 Trend Analysis of Corrib Flows

The Wolfe Tone AM flood flow series record suggests that there is significant increasing trend in the AM flows in the Corrib from the 1950's to present time. However, examination of record from 1972 onwards does not suggest any significant change, which is the record period post the majority of the Arterial drainage works on the Corrib Catchment. On the River Clare, the Corrofin gauge AM flood flow record from 1954 onwards suggests significant increasing trend most likely due to the Arterial Drainage Works. However, the Ballygaddy gauge on the Clare (for the period 1974 onwards) post arterial drainage, suggests no significant trend in the AM series and the Claregalway gauge record is too short to draw any conclusions. The Lough Corrib lake gauges which are post drainage scheme (Cong and Annaghdown provide records from 1972 onwards) and the Dangan River Corrib gauge (1986 onwards) show no significant trend at the 90-percentile or greater significance.

In conclusion, the time series of annual maximum floods both parametric (flood level and flow rate magnitude) and non-parametric (flood ranking index) for the AM series examined generally display increasing trends in the flood magnitude with time. In many of the AM series that captured both pre and post arterial drainage works some of this increasing trend is clearly due to these drainage works. However, the continued trend in increased flood events and their magnitudes in the post arterial drainage record period suggests that other sources, such as, land-use changes (agricultural drainage of the catchment, forestry loss of peatlands, etc.) and climate change are having an influence. Statistically the significance of this more recent trend post arterial drainage works cannot be proved at 90% or greater significance without a longer record period.

The record period for gauged tidal flood levels within inner Galway Bay was too short to establish any significance trend. However, it is noted that the three largest tidal floods have occurred in the past decade.

1.10 Recommendations

It is recommended that the climate change allowances of 20% and 30% increase at the MRFS and the HEFS be included for both storm rainfall and flood runoff in assessing the adaptation of the proposed flood relief scheme to future change. The sea level rise of 500mm and 1000mm associated with the MRFS and the HEFS cases be included in assessing the adaptation of the proposed coastal and estuarine flood relief measures. Future potential catchment land-use changes, agriculture and forestry are not considered for the Corrib catchment to be significant drivers for increase in the design flood magnitudes and changes to the hydrograph shape through Galway City. The potential impact of local urbanisation to runoff rates within potential defended lands will require careful consideration, particularly where temporary storage or pumping of storm flows from the defended areas might be required.

It is recommended to include for hydrological uncertainty in respect to Corrib design flows and the tidal flood levels allowances based on measurement, model and statistical error. These increases in the design flood flow and tidal height magnitudes should be tested in the sensitivity analysis of the hydraulic design.

Table 1-1 Return Period Design Corrib Flood Flows and Tidal Flood Level

Return Period T years	2	5	10	20	50	100	200	1000
Corrib Flood Flow Q_T (m ³ /s)	255.7	304	335.7	366.4	406	435.7	465.3	533.8
Q_T Uncertainty allowance (m ³ /s)	34.8	46.9	54.8	62.4	72.4	79.7	87.2	104.3
Tidal Flood Level H_T (m OSGM15)	3.19	3.37	3.49	3.60	3.76	3.87	3.98	4.25
H_T Uncertainty allowance (m)	0.11	0.13	0.14	0.16	0.18	0.19	0.21	0.25

2 Introduction

2.1 Background

The Office of Public Works (OPW), in partnership with Galway City Council (GCC) have completed a Catchment Flood Risk Assessment and Management Study (CFRAMS) for the Corrib Catchment, which includes the Galway City Area. The Catchment Flood Risk Management Plan (CFRMP), which was published in 2018, concluded that a flood relief scheme for Galway City would be viable and effective.

Arising from the CFRMP, Galway City Council in association with the OPW have commissioned Arup to develop a flood relief scheme for Galway City. The project will consist of five stages as follows:

- Stage I: Identification and Development of a Preferred Scheme
- Stage II: Public Exhibition/ Planning Process
- Stage III: Detailed Construction Design, Compilation of Work Packages and the Preparation of Tenders for Contracts and Confirmation Documents
- Stage IV: Construction Supervision & Project Management Services
- Stage V: Handover of Works

The project title of the Galway City Flood Relief Scheme (FRS) is Corrib go Cósta and the Hydrology Report is produced as part of Stage I of the project. The Hydrology Report provides the design flood conditions for the Flood Relief Scheme in respect to identifying and developing the preferred scheme under Stage I of the project. Hydro Environmental Ltd. In association with ARUP was responsible for the preparation of the hydrology report.

The hydrological analysis in combination with the hydraulic flood modelling considers the flood risk emanating from the River Corrib, its local tributaries, drainage areas, estuary and coastal waters on the city of Galway. The hydrology study establishes best estimates of return period flood flow magnitudes and associated flood hydrographs within the Galway City Flood Relief Scheme Area from the Corrib and associated tributaries. The study also examines the tidal risk on the city from Galway Bay in respect to extreme storm surge levels and potential combination effects with fluvial and pluvial flood and storm events. These fluvial, pluvial and tidal flood estimates are required as inputs to the hydraulic flood model of the estuary, river network and floodplain areas within the FRS area to determine the respective flood levels, flow depths and velocities and flooding duration. The FRS area is the area within the red line boundary presented in Background Map Data © 2023 Google, DigitalGlobe

Figure 2-1 and extends upstream to the outlet from Lough Corrib.

Please note for clarity that all levels stated as m OD Malin are to the current OGSM15 geoid model datum unless otherwise stated. Other datums referred to in the report for historical reasons are Poolbeg datum and OGSM02.



Background Map Data © 2023 Google, DigitalGlobe

Figure 2-1 Galway City Flood Relief Scheme Area Boundary

2.2 Corrib Catchment


2.2.1 General description

The main river flowing through Galway City is the River Corrib which flows from Lough Corrib southwards to sea at Galway Port. The lower reach of the Corrib downstream of the OPW salmon weir barrage in Galway City is tidally influenced. The estuarine / transitional reach of the Corrib open to the sea is downstream of Wolfe Tone Bridge in the Claddagh basin, refer to Figure 2-2. The tidal backwater from the claddagh basin impacts water levels in the river reach from Wolfe Tone Bridge to upstream of the Salmon Weir Bridge and just downstream of the OPW Sluice Barrage.

The River Corrib channel from the Lough Corrib to the sea is a significantly modified channel through human engineering intervention and is very much canalised through Galway City. The Corrib Navigation and Drainage Works in the period 1848 to 1858 excavated a new wide outlet channel from Lough Corrib known as “The Friar’s Cut” which provides a more direct shorter and deeper channel (1.3km in length) to drain the lake than the former, meandering old channel of almost 3.8km in length, which is still present today. The “Friar’s Cut” channel is the main flow conduit from the Lake, refer to Figure 2-4. The Friar’s Cut” extends into the lake to meet the deeper navigable waters. As part of the Corrib Navigation and Drainage Works (1848 to 1858) the canal system in Galway was constructed including the main Eglinton Canal.

Significant excavation of the River Corrib channel has taken place both during the original Corrib Drainage and Navigation Scheme (1848-1858) and also during the OPW Corrib-Clare Arterial Drainage Scheme (in the late 1950’s and early 1960’s). The River Corrib channel is a navigation channel and is reasonably wide, varying typically from 80m to 130m between riverbanks and typically 3 to 4m deep in the navigation section of the channel. It is an impounded channel with levels maintained generally close to 6m OD Malin throughout the year by gated sluices at the Salmon Weir barrage that is operated by the OPW Arterial Drainage Section.

The catchment area of the River Corrib based on the EPA Hydrotool and the OPW FSU Physical Catchment Descriptor Data (based on DTM elevation data) is estimated at 3,136km² to Wolfe Tone Bridge, 3121km² to the Dangan Slip Hydrometric gauge, refer to Figure 2-3 for catchment map. This catchment is quite large by Irish standards and is the biggest river system in the Western River Basin District and is the sixth largest river catchment on the island of Ireland (i.e., Shannon(15,700km²), Bann (5,810 km²), Erne (4,370 km²), Suir (3,610km²), Blackwater (3,330km²) and Corrib(3,140km²)).



Hydro
Environmental Ltd





Figure 2-3 River Corrib Catchment Map to Wolfe Tone Bridge



Background Map Data © 2023 Google, DigitalGlobe

Figure 2-4 *Corrib Arterial Drainage Channel*

The EPA register of hydrometric gauges gives a catchment area to Wolfe Tone Bridge of 3111km² which is less than the FSU/EPA catchment estimate of 3136 km². The catchment extents were reviewed as part of this study and currently the catchment estimate of 3136 km² (EPA Hydro Catchments estimate from the EPA Water Maps) which includes the small Terryland stream catchment of 9.04km² in area, refer to Figure 2-5. This basin area should be excluded as the Terryland stream drains underground via karst swallow-holes at Castlegar Galway City, through the karst limestone bedrock to the sea and does not contribute to the Corrib river flow at Terryland water intake. In fact, the Corrib contributes a small abstraction to the Terryland Stream via the public water intake channel at the Dike Road near Jordan's Island which supplies the water treatment plant and any excess flow discharges to the Terryland River. A review of the mapped catchment area of the River Corrib to Wolfe Tone Bridge estimates a catchment area of 3,126.2 km² when Terryland catchment is removed and slight adjustments to the watershed boundary are made.




Figure 2-5 Terryland Stream catchment area of 9km² discharging to the sea via swallow-holes at Castlegar.

The River Corrib channel acts as a short outflow channel from Lough Corrib to the sea at the Claddagh Basin measuring just under 6.4km in length from the lake outlet at Friar's Cut to Wolfe Tone Bridge at the Claddagh Basin. The tidally influenced section extends from the downstream of the Salmon Weir to the Galway Port navigation channel south of Nimo's Pier. The downstream channel from the Salmon Weir to Claddagh basin was excavated into the bedrock as part of the arterial drainage scheme to convey Corrib flow and prevent

backwatering of the weir under design flood conditions. This reach section is much steeper than the upstream channel section at a typical bed gradient of fall of 1m in 275m.

2.3 Galway Salmon Weir Sluice Barrage

The River Corrib flow is regulated by the Salmon Weir Sluice Barrage located opposite Earl's Island and Woodquay area of Galway City. The barrage was constructed by the OPW as part of the Corrib-Clare Arterial drainage scheme in 1959 and consists of 14 steel hydraulic gates along with 2 older wooden lift gates from the previous weir control. The weir is an arc of 114.8m in length and total gate openings width of 91.7m (c. 80% of the length). The weir discharges to a sloping concrete spillway apron which is designed as an energy dissipator to generate a hydraulic jump within the protected apron area downstream of the weir crest. The 14 gates are hinge gates that are lowered by tilting forward from their sill and are operated hydraulically.

A detailed paper on the Galway Salmon Weir Sluice Barrage by Arthure (1960) describes the design and construction of the new barrage which was completed in 1959 and gives details of the previous weir which was constructed in 1852 by the Board of Public Works (triangular plan weir) as part of the original Corrib drainage and navigation scheme. The former weir was a massive structure built from limestone blocks and had a total length of 607 feet (185m) and an average crest level of 27.7 ft OD Poolbeg (c. 5.702m OGS15) in a triangular plan profile. Falling boards, 15inches in depth, were provided over 190ft of the weir and two 10ft vertical lift timber sluice gates (which are still present today) formed the western terminus.

The new barrage as constructed consisted of 14no. leaf type steel sluice gates which are arranged in a circular arc. The gates measure 20ft in width (6.096m) and 5ft in height (1.524m). The crest level of the weir when the gates fully closed is set at 28ft O.D Poolbeg (c. 5.79m OD Malin OGS15) and when fully opened the gates are hinged at their base and are reclined to the horizontal where they fit into a recess in the concrete floor. The crest level of the weir when gates are fully open (i.e., recessed into the gate bucket) is 23 ft Poolbeg (4.269m OGS15). Murphy Survey as part of the infill topographical survey for the project confirmed that the crest level of the gates when fully closed varied very slightly over the 14 gates with crests levels measured at 5.76 to 5.79m OGS15.

The two 10ft vertical lift timber sluice gates and masonry abutments from the former regulating weir were retained at the western terminus. The invert level of these timer gates was surveyed by Murphy Surveys at 4.37m OGS15. A fish pass and two elver passes were incorporated in the weir configuration. The gates are operated by means of hydraulic rams and when in the desired position a hydro-loc valve is applied which prevents the gate from opening further. A gate can be opened or closed in 3.5minutes. Essentially the function of the weir control is to open-up to allow floodwaters pass downstream without causing upstream flooding and to close in non-flood periods in order to maintain upstream river and lake levels for navigation purposes and also to maintain water levels in the canals for hydropower (milling).

Arthure described in his detailed paper the design requirements of the weir (14 steel and 2 timber gates) to discharge a peak of 10,000cusec (283cumec) and maintain the upstream water level at the weir at 28ft Poolbeg. A full-scale physical model was developed of a single full gate with abutments and half gates on either side. Based on the results from the physical model a total flow 9000 ft³/s (254cumec) discharging through the 14 gates would require an upstream water level of 28ft Poolbeg. Based on the critical depth equation for a broad crested weir, which would represent the gate when fully opened, gives a coefficient of discharge Cd of 0.93 which is reasonably consistent with the literature.

A report by the Farrell et al of the OPW (May 1987) into the operation of the Galway Sluice barrage states that the design was to maintain the water level in Lough Corrib at or above 28ft OD Poolbeg (i.e., 5.79m OGSM15) and at or below 30ft OD Poolbeg (i.e., 6.403m OGSM15). This paper also showed that maintaining levels below 30ft OD in Lough Corrib could not be achieved with only 4years out of 27years examined achieving this upper limit. The conclusion of the study found that the fault of such exceedances in lake flood levels did not lie with the capacity of the Weir gates but with the capacity of the Corrib channel between the Lake and the gates requiring a sufficient flow depth and fall between the lake and the weir to discharge flood flows from Lough Corrib.



Plate 1 *View of Salmon Weir taken on the 11 December 2015 during flood conditions with all gates opened*



Plate 2 *View of the two timber lift/drop gates taking during flood flows on the 11th December 2015*

2.4 Lough Corrib

2.4.1 Lakes within the Corrib Catchment

The Corrib River system includes a total lake surface area of approximately 285km². The larger lakes are Lough Corrib (166km²), Lough Mask (82km²) and Lough Carra (15.6km²) and smaller lakes of, Nafooney (2.5km²), Ross (1.4km²), Bofin (0.9km²) and Lettercraffroe (0.8km²) loughs and a further 465 smaller lakes from 0.1ha to 70ha within the catchment. The combined effect of these lakes provides significant attenuation storage limiting winter flood flows and sustaining summer low flows in the Corrib.

2.4.2 Inflow Tributaries to Lough Corrib

The main river tributaries discharging into Lough Corrib are presented below and their catchment extents are presented in Figure 2-6:

- Lough Mask Outflow via the Cong Canal (also potential for significant groundwater flow in the epi-karst between the Mask and Corrib (catchment area 892 km² of Mask outflow))

Eastern Side of Corrib with the Limestone Bedrock area

- Cross River (66.2km²)
- The Black River which flows through Shrle Village (Catchment Area 204km²)
- The Headford River (Catchment Area 45km²)
- The Cregg River (Catchment Area 61 km²)
- Clare River flows through Claregalway Village Catchment Area 1108 km² to Lough Corrib and 1083.1km² to Claregalway Bridge)

Western Side of Corrib from the igneous bedrock formations

- Habhain Cor Na Mona River (Catchment Area 26km²)
- Habhain Thir Na Cille (Catchment Area 85km²)
- Owenree River (Catchment Area 23km²)
- Owenriff River through Oughterard (Catchment Area 67km²)
- Aughnanum River (Catchment Area 29km²)
- Loch an Chip River (Catchment Area 89km²)




Figure 2-6 Main Catchments to Lough Corrib

2.5 Tributaries discharging to the River Corrib downstream of the Lake

There are no major tributaries discharging to the Corrib within the scheme area downstream of Lough Corrib with the Corrib catchment area from the old river confluence with Friars Cut to Wolfe Tone Bridge only increasing by 7km² which represents an increase of 0.6% in total catchment area. The catchment area discharging to the old River between the Lake and the confluence with the Friars Cut channel is estimated to be 97 km² in area which includes Lough Kip River and the much smaller Drum and Gortatleva Streams. Small local inflows occur from karst groundwater fed springs at Menlough and from the Coolagh Lakes and at Dangan from the Bushypark stream.


The canal system in Galway city is principally fed by the River Corrib upstream of the Salmon Weir with no other major tributary inflowing to the canal system except for a number of small storm pipes. The Distillery channel through the University is fed by Sruffaunacashlaun Stream that drains the Ragoon, Shantalla and Westside area of Galway City, and also fed by a number of storm sewers from the upper Newcastle area and the Dangan Area. The Sruffaunacashlaun Stream has, based on lidar and the drainage network extracted from historical 25inch mapping, a catchment area to the Distillery Stream of c. 2.5km². The catchment for this stream to its confluence with the Distillery Stream is presented in Background Map Data © 2023 Google, DigitalGlobe

Figure 2-7. This catchment is now completely urbanised, and its runoff features dictated by the Galway City stormwater drainage network. The Distillery Stream through the University campus also receives inflow from the Corrib via the Kingfisher channel which is controlled by Penstocks and also downstream of Earl's Island by the Huntsman canal discharge. The distillery channel which historically was channelised for milling is contained within its own walled channel discharging to the Corrib River in the reach downstream of the Salmon Weir Bridge and just upstream of O'Brien's Bridge.

The Terryland Stream also known as the Sandy River has an estimated catchment area of 9km², which is karstic and this small river is principally fed by the groundwater table and by storm sewer outfalls from the Lisbaun and Terryland urban areas and the Tuam Road and Twomileditch area. Originally before the Corrib drainage and navigation scheme in the 1850's the Corrib would have flooded into the Terryland basin, but this connection has since been cut off by the Dike Road embankment, constructed originally in the 1850's and improved by the OPW as part of the Corrib-Clare arterial drainage scheme. The Terryland River channel is an OPW maintained drainage channel that discharges to swallow-holes at Castlegar.

A large section of the mapped drainage catchment area in Figure 2-5 in the vicinity of Ballindooley Lake basin and the Ballybrit, Parkmore and Twomileditch area are not very well connected to the Terryland Stream with these areas draining slowly to the regional groundwater table and therefore not contributing significantly to flood flows in the Terryland

stream, refer to Figure 2-8. These areas potentially only contribute as general groundwater baseflow to the Terryland Basin. As a consequence, the effective surface runoff catchment of the Terryland Stream is only 4.58km² (i.e., over 50% reduction in the mapped total drainage area), refer to Figure 2-9.



Background Map Data © 2023 Google, DigitalGlobe

Figure 2-7 *Sruffaunacashlaun Stream catchment area from Lidar mapping*




Figure 2-8 Terryland Drainage Basin Contour Map and Features




Figure 2-9 Terryland Stream Surface Drainage Area Contributing to flood flows

3 Data Collection

3.1 Introduction

Various datasets relevant to catchment hydrology of the Corrib have been collated for inclusion in the hydrological assessment of catchment flood flows within the Study Area. These datasets are summarised as follows:

EPA

EPA hydrometric data sets

EPA river network mapping (OSi Geometric River Network)

Corine Land-use mapping (2018)

EU

Copernicus EMS mapping

Geological Survey of Ireland

Soils and subsoil mapping

Bedrock mapping

Groundwater recharge mapping

Aquifer mapping

Aquifer vulnerability mapping

Karst features mapping

Groundwater Flooding Mapping

Recharge Rate Mapping

Local Authority – Galway City Council (GCC)

Historical flood information

Storm drainage catchments and storm, foul and combined sewer network details

Planning and development information in respect to current and urban footprint

Met Eireann

Gauged rainfall data from Synoptic Stations and daily rainfall gauging stations for the Corrib–Hydrometric Area 30 and Galway and Mayo areas

Seasonal Average Annual Rainfall (SAAR) – 2km grid model

Storm Rain Depth-Duration-Frequency model – 2km grid dataset

OPW

OPW hydrometric data at relevant gauges described latter refer to Section 4.3 for list of gauging stations

OPW FSU Physical Catchment Descriptor data set

OPW gauged hydrometric catchment boundaries

OPW CFRAM river survey cross-section data

OPW CFRAM reports for the Western Basin units of management 29, 30 and 31 and Galway City AFA.

OPW historical flood data flood inundation mapping ()

OPW Lidar Digital Terrain Mapping (DTM) 2m, 5m and 10m grids for the Galway City area

OSI

Vector mapping datasets

Historical OSI mapping

Orthographic mapping

OSi PRIME-2 dataset

OSI Geometric River Network: 24/02/2020 GIS shapefile

Local Authorities

Galway City Council

City Development Plan

Planning Application web site

Urban Storm Drainage network

Galway Co. Council

County Development Plan

Planning Application web site

Other Bodies

Galway Port Company

Wave and Tide data

NUI Galway

Strategic Flood Risk Assessment of University Campus

Marine Institute

Tide data and astronomical tidal Predictions

Irish Water

Foul and combined Sewer network

Terryland abstraction and proposed Corrib new Abstraction

3.2 Hydrometric Gauges

The Corrib catchment has numerous hydrometric gauges present within its catchment refer to Figure 3-1 below. Many of these gauges provide level only data generally associated with the various lake gauges. Hydrometric stage and flow gauging stations are present on the Corrib at Wolfe Tone Bridge, on the Clare River at Claregalway, Corofin and Ballygaddy Tuam, on the Owenriff at Oughterard and on the Cong Canal at Cong Weir. Within the Galway City Scheme Area there are a number of water level (Stage) stations present which provide relevant water level data for the hydraulic model calibration and validation exercise, refer to Figure 3-2 for their general location. These gauges are located at Galway Port, Wolfe Tone Bridge, upstream of the Salmon Weir Barrage and a recently installed recorder at the Quincentennial Bridge and the existing hydrometric station at Dangan Slip and at Angligham in Lough Corrib near the lake's outflow at Friar's Cut. A water level recorder as part of this project has recently been installed by the OPW on the Terryland Stream which picks up the tidal response of the Terryland from its swallow holes and confirms groundwater connection to Galway Bay. A new water level recorder as part of this study has been installed by the OPW in the Corrib River channel a short distance downstream of the Salmon Weir Barrage (30097) adjacent to Earl's Island.

The available Met Eireann rain gauges for the Corrib Catchment are presented in Figure 3-3. These are daily read recorders and have different start and end periods. The daily rainfalls from these gauges is extracted for the more significant historical flood events where coverage is available, and the rainfall return periods for such events are estimated.

The majority of rain gauges are only daily read gauges, with hourly records only available at two gauges, Mace Head Gauge in Connemara and at Atherry Gauge.




Figure 3-1 Relevant Hydrometric flow and water level only Gauging Stations within Corrib Catchment




Figure 3-2 Hydrometric flow and water level only Gauging Stations within Galway City Scheme Area




Figure 3-3 Daily Read Rain Gauges for the Corrib Catchment

3.3 Review of Physical Catchment Descriptor datasets

The OPW Flood Study Update (FSU) physical catchment descriptors data set for gauged and ungauged river nodal points has been provided along with catchment and sub-catchment boundaries and the OSI river channel network. As per Section 2.4.2 and 2.4.4 of the hydrology brief all of the relevant data bases have been included with their most up to date versions, including the OSI Geometric River Network: 24/02/2020 GIS shapefile. This data was reviewed for any significant discrepancies which may be present due to mapping error or catchment land use changes or temporal changes in a data set such as changes in the long-term rainfall. The Catchment boundaries have been checked against DTM and the OSI drainage network polylines checked for inconsistencies. These have been found to be generally suitable for the large-scale catchment of the River Corrib to Galway, but at the smaller local scale significant revisions to the catchment extents and watershed boundary have been applied in respect to the Terryland Stream and Sruffaunacashlaun Stream and the resultant changes to the Corrib catchment at the various selected HEP nodal Points.

The selected HEP's for the Scheme area have been presented latter in Section 11 and involve 22 nodal points, with 15 on the Corrib River, 5 on the Terryland River and 2 on the Sruffaunacashlaun Stream, refer to Background Map Data © 2023 Google, DigitalGlobe

Figure 11-1.

The PCDs were checked for consistency within the Scheme area between upstream and downstream HEPs and slight adjustments were made for the Corrib in respect to catchment Area. The river mainline slope parameter S1085 was found to fluctuate somewhat between nodes within the study reach which will cause a fluctuation in the estimated design flow magnitudes as all other PCD parameters used in the FSU PCD flood estimation equation are relatively constant with catchment area only slightly increasing in the downstream direction. This jumpiness in flow rate between nodes is not considered realistic for such an attenuated catchment. This is examined further in in Section 11 with a recommendation to use a constant average S1085 value over the study reach to eliminate inconsistency in the estimated flows between nodes.

For the Terryland and Sruffaunacashlaun Streams the FSU PCD's values had to be completely revised from available mapping as the Terryland actually flows in the opposite direction than assumed in the FSU and Sruffaunacashlaun Stream was never included. The revised PCD values for all 22 HEPs are presented in Table 11-1 and Table 11-2.

3.4 CFRAM review

The Western Catchment Flood Risk Assessment and Management (CFRAM) Study was one of seven River Basin District studies carried out across the Republic of Ireland from 2011 to 2016 carried out nationally to meet the requirements of the EU Floods Directive (Directive

2007/60/EC) and the 2004 Flood Policy Review Report. The Galway City Area was included in the CFRAM assessment under Unit of Management (UoM) 30 (Corrib Catchment, Hydrometric Area 30). The CFRAM study included detailed hydrological and hydraulic modelling assessments to quantify the flood risk from fluvial and coastal sources and to identify management measures to protect vulnerable receptors within the AFAs.

The following Table 3-3 presents the return period design flows produced by the CFRAM study for the Corrib at Galway City based on the FSU physical catchment descriptor (PCD) Median flood flow equation and using the FSU pooled growth curve and fitted by a three parameter GLO distribution. The pivotal gauged site used in the CFRAM study was the Wolfe Tone Station (30061) with a QMED = 248cumec based on the available 31-year record from 1972 to 2002. The CFRAM pooling group was selected based on the FSU methodology from the most hydrologically similar gauged stations to the subject site using the PCD descriptors of AREA (3136km²), SAAR (1422mm) and BFI_{soil} (0.81) to produce 500station years of AM flows. The distribution was fitted by the method of l-moments. This gave a 100year flood growth curve of 1.78 and 2.33 for the 1000year return period.

The CFRAM study concluded that single at-site analysis of the Corrib AM series at Wolfe Tone Bridge with 31years of AM flows available was not suitable for estimating the larger return period flood flows as the record available was from hydrometric year 1972 to 2002 which missed the 1968 flood and the more recent large floods including 2006 and 2009 flood. The Wolfe Tone bridge gauge was also not included in the CFRAM pooling group selection due to it relatively short record length of 31years and poor flood rating.

Table 3-1 **CFRAM Statistical Distribution Type and parameters for River Corrib at Galway**

Distribution	Location	Scale	Shape	100yr Growth factor
Pooled GLO (L-moments)	1.000	0.132	-1.04	1.780

Table 3-2 Pooling Group Selected by the CFRAM study for the River Corrib (it is based on the FSU web portal selection of sites)

Station ref	Rank	Watercourse Location	Years
34001	1	Moy Rahans	37
34003	2	Moy Foxford	36
12002	3	Slaney Enniscorthy	31
12001	4	Slaney Scarawalsh	55
27002	5	Fergus Ballycorey	56
35073	6	Lough Gill	30
16011	7	Suir Clonmel	57
26108	8	Boyle Abbey Bridge	20
35012	9	Garvogue New Bridge	10
16009	10	Suir Caher Park	57
35005	11	Ballysadare	62
25017	12	Banagher	39
26005	13	Suck Derrycahill	56
Station years			546

Table 3-3 CFRAM estimated Return Period flows and Growth Factor for the Corrib at Wolfe Tone Bridge

Return Period (years)	2	5	10	20	50	100	200	1000
AEPs	50%	20%	10%	5%	2%	1%	0.5%	0.1%
Flow (cumec)	248	296.8	328.8	360.8	405.0	440.9	479.1	579.0
Growth Factor	1.00	1.20	1.33	1.45	1.63	1.78	1.93	2.33

The CFRAM study noted the following in respect to the selected pooling group:

“The Corrib catchment at Galway is unusual as it is very large and subject to extremely large flood attenuation due to the size of Loughs Corrib and Mask immediately upstream. For this reason, it is difficult to have much confidence that many of the gauges in the pooling group are representative of the hydrological response of the Corrib catchment. The top-ranking gauges in the group are both on the Moy, which has a similar size to the Corrib and is also subject to major influence from loughs, although a substantial part of the Moy catchment does not drain through the loughs.”

The CFRAM study has a high degree of uncertainty associated with its return period flood estimates due to using a QMED estimate based on the Wolfe Tone gauge whose rating relationship was not reviewed and since considered no longer valid by OPW hydrometric, and which ceased in 2002 missing out on the more recent decades of larger flood events. This uncertainty was compounded by the pooling group selection which had a wide variety of catchment types in the group, the majority of which did have significant lake attenuation within their catchments. A GLO frequency distribution was selected, which is unclear from the study

whether it was the best choice of distribution for the pooling group. It is demonstrated later in Section 5 of this report that Q_{med} for the Corrib is actually higher than CFRAM estimate, at 265.25cumec and that the recommended pooled flood growth curve is milder and that the most suitable statistical fit to the pooling group is produced by a 2-parameter EV1 distribution as opposed to a GLO distribution.

The design flood hydrograph developed in the CFRAM study for the Corrib at Galway used the FSU hydrograph width method with the width set to the median width of the observed hydrographs for the pivotal gauged site at Wolfe Tone Bridge. This method included 20 flood events from the recorded period of 1972 to 2002 with the largest event producing an estimated peak flow of 441cumec on the 25 January 1975. The hydrograph parameters produced by this method gave a n value of 2.20 and a T_r of 101hours.




Figure 3-4 *CFRAM Design Hydrograph Shape for the Corrib at Wolfe Tone Bridge from HWA and the FSR time to peak and design storm method included for comparison*

This hydrograph Shape developed by the CFRAM study is not very realistic for the River Corrib which is significantly slower to rise and recede with the peak flow almost steady over many days due to the attenuating effect of its Lakes and the karst groundwater catchments to the east. A more realistic longer duration hydrograph in this study was produced and validated against the more recent large floods of 2009, 2015/2016 and 2020, refer to Section 9.

3.5 Hydrogeology and Groundwater

The Geological Survey of Ireland groundwater mapping provides information on bedrock, aquifers, aquifer vulnerability, quaternary sediments and groundwater recharge which are presented for the Catchment in Figure 3-5 to Figure 3-8. The Corrib catchment primarily consists of Limestone Bedrock formations representing 81% of the catchment area and the remaining 19% is underlain by the more impervious igneous bedrock located on the western side of the Corrib. The Geological Survey of Ireland Aquifer classification indicates that 67% of the total catchment area is underlain by a regionally important karstified Limestone Bedrock with conduit flow. This karstified bedrock provides for high groundwater recharge and storage within the bedrock which generally attenuates the shorter duration flashier floods with flooding in the turloughs and rivers associated with the more prolonged rainfall events that generally peak between late autumn and early spring. Presented in Figure 3-9 is the Corine 2018 Land-use mapping. The OPW Arterial Drainage scheme channels and benefitting lands mapping for the Corrib catchment is presented in Figure 3-10, which shows a significant area of the Corrib catchment being arterially drained.




Figure 3-5 *Bedrock Aquifer within the Corrib Catchment*




Figure 3-6 Groundwater Vulnerability within the Corrib Catchment




Figure 3-7 Quaternary Geology of the Corrib Catchment




Figure 3-8 Groundwater Recharge mapping for Corrib Catchment (mm per annum)




Figure 3-9 Corine 2018 Land Use mapping for Corrib Catchment




Figure 3-10 OPW Arterial Drainage Channels and benefiting Lands